



Cal. 2620A



131 262



231 260



241 262



261 260



☆270 262



☆271 262



281 261



282 262



☆354 261



☆354 263



383 260



384 261



387 261



389 260



391 260



436 261



491 260



493 260



495 260



701 260



706 260



☆4001 262



4002 261



4146 260



4216 260



4219 261



4239 260



4242 260



4270 260



4455 260

011 409



☆SEIKO SB-DL



012 151



012 159



012 459



012 768



017 125



017 126



017 127



017 129



017 131



017 132



017 159



017 936

2/1

Cal. 2620A

Characteristics:

Casing diameter: ϕ 17.60 mm
 Maximum height: 3.00 mm without battery
 Jewels: 2 j
 Frequency of quartz crystal oscillator: 32,768 Hz (Hz=Hertz Cycle per second)
 Driving system: Step motor system (2 poles)
 Regulation system: Trimmer condenser

PART NO.	PART NAME	PART NO.	PART NAME
131 262	Third wheel bridge	4239 260	Rotor stator
231 260	Third wheel & pinion	4242 260	Plus terminal of battery connection
241 262	Fourth wheel & pinion	4270 260	Battery connection
261 260	Minute wheel	4455 260	Reset lever
☆ 270 262	Center minute wheel with cannon pinion (1.74 mm)	011 409	Upper hole jewel for step rotor
☆270 265	Center minute wheel with cannon pinion (2.26 mm)	011 409	Lower hole jewel for step rotor
☆270 266	Center minute wheel with cannon pinion (1.84 mm)	012 151	Third wheel bridge screw
☆270 267	Center minute wheel with cannon pinion (2.85 mm)	012 151	Circuit block screw A
☆270 274	Center minute wheel with cannon pinion (1.74 mm)	012 151	Coil block screw (Screw for plus terminal of battery connection)
☆270 275	Center minute wheel with cannon pinion (2.26 mm)	012 159	Circuit block screw B
☆270 276	Center minute wheel with cannon pinion (1.84 mm)	012 459	Case screw
☆270 277	Center minute wheel with cannon pinion (2.85 mm)	012 768	Setting lever axle spring screw
☆ 271 262	Hour wheel (0.85 mm)	012 768	Minute wheel bridge screw
☆271 266	Hour wheel (0.95 mm)	017 125	Tube for circuit block A
☆271 267	Hour wheel (1.37 mm)	017 126	Tube for circuit block B
☆271 268	Hour wheel (1.91 mm)	017 127	Tube for circuit block C
281 261	Setting wheel	017 129	Tube for third wheel bridge screw A
282 262	Clutch wheel	017 131	Tube for coil block screw
☆ 354 261	Winding stem (13.13 mm)	017 132	Second setting lever pin
☆ 354 263	Winding stem (18.58 mm)	017 159	Tube for third wheel bridge screw B
383 260	Setting lever	017 936	Eccentric dial pin
384 261	Yoke (Clutch lever)	☆SEIKO SB-DL	Silver peroxide battery
387 261	Minute wheel bridge		
389 260	Setting lever axle spring		
391 260	Second setting lever		
436 261	Lower end-piece for third wheel		
491 260	Dial washer		
493 260	Hour wheel ring (Gold, 0.03mm thickness)		
493 261	Hour wheel ring (Silver, 0.05 mm thickness)		
493 262	Hour wheel ring (Gold, 0.10 mm thickness)		
495 260	Spacer for third wheel bridge		
701 260	Fifth wheel & pinion		
706 260	Sixth wheel & pinion		
☆ 4001 262	Circuit block		
☆ 4001 270			
4002 261	Coil block		
4146 260	Step rotor		
4216 260	Insulator for battery		
4219 261	Insulator for battery connection		









☆⇒ Please see remarks on the reverse page.
 Part numbers in light letters are not shown in photos.

Cal. 2620A

Remarks:

Center minute wheel with cannon pinion, Hour wheel

Combination:

Type	a		b		c		d	
Center minute wheel with cannon pinion		Gold plated		Gold plated		Gold plated		Gold plated
	☆270 262	☆270 274	☆270 265	☆270 275	☆270 266	☆270 276	☆270 267	☆270 277
Hour wheel								
	Silver		Silver		Gold		Silver	
	☆271 262		☆271 267		☆271 266		☆271 268	

Winding stem.....Refer to the photograph on the front page.

- ☆354 261.....Short winding stem (Thread is provided completely on the crown portion.)
- ☆354 263.....Long winding stem (Thread is provided only on the end of the crown portion.)

If the combination of the winding stem and case is unknown, check the case number and refer to "SEIKO Quartz Casing Parts List" to choose an appropriate winding stem.

Circuit block

- ☆4001 262.....4001 270 can be used as 4001 262.
- (☆4001 270)

Coil block

- ☆4002 261.....The parts that have the same parts No. as 4002 261 are interchangeable, even if the color of that parts is different.

Battery

- ☆SEIKO SB-DL.....The applied battery for this calibre might be added the substitutive in the future. In that case, please refer to separate "BATTERIES FOR SEIKO QUARTZ WATCHES".