



Calibre No.	6106A	Jewels	25j	Style Name
-------------	-------	--------	-----	------------



Cal. 6106A



Characteristics

- Casing diameter : 27.00 ϕ mm
- Maximum height : 5.15 mm
- Vibrations per hour : 21,600
- Automatic winding with sweep second
- Calendar (day & date)
- Pushing instant date setting
- Second-setting device
- "Diashock" Shock Resistant Device

112611	122611	161805	171611	205613	213612	401615	224611	225611	
231610	241611	251611	301611	310611	315611	331610	341611	345611	261611
271611	281611	282611	285611	381611	383611	384611	387611	388611	
391610	☆ 397610	014363	014364	014365	011210	014317	354615	505611	823611
831611	839610	632610	802610	810610	817610	868610	880610	808610	
883610	963610	193612	500613	☆ 870610	☆ 801610	☆ 801612	☆ 884611		

022150	022252	022257	022266	022351	022467	022468	022469
							2/1
022470	022471	022662	022677	022758	022760	022773	

☆ ⇨ Please see remarks on the reverse page.

Calibre No.	6106A	Jewels	25j	Style Name
--------------------	--------------	---------------	------------	-------------------

PART NO.	LIST OF MATERIALS	PART NO.	LIST OF MATERIALS
112611	Barrel & train-wheel bridge	☆ 801610	Date dial
122611	Center wheel bridge	☆ 801612	
161805	Pallet cock	802610	Date driving wheel
171611	Balance cock	808610	Date dial guard
193612	Framework for automatic device with ball-bearing	810610	Date jumper
205613	Complete barrel with arbor	817610	Intermediate date wheel
213612	Barrel arbor	868610	Day finger
224611	Center wheel & pinion with cannon pinion	☆ 870610	Day star with dial disk (English letters)
225611	Cannon pinion	880610	Date corrector
231610	Third wheel & pinion	883610	Date corrector spring
241611	Sweep second wheel & pinion	☆ 884611	Holding ring for dial
251611	Escape wheel & pinion	963610	Snap for day star with dial disk
261611	Minute wheel	022150	Stud screw
271611	Hour wheel	022252	Holder screw for transmission wheel & pawl lever
281611	Setting wheel	022257	Date corrector spring screw
282611	Clutch wheel	022266	Minute wheel bridge screw
285611	Ratchet wheel	022351	Center wheel bridge screw
301611	Jewelled pallet fork & staff	022467	Ratchet wheel screw
310611	Balance complete with stud	022468	Pallet cock screw
315611	Balance staff	022469	Bridge screw
331610	Roller with jewel	022470	Framework screw for automatic device with ball-bearing
341611	Regulator	022471	Click screw
345611	Stud holder	022662	Setting lever spring screw
354615	Winding stem	022677	Screw for day & date driving wheel
381611	Click	022758	Dial screw
383611	Setting lever with axle	022760	Date dial guard screw
384611	Yoke (Clutch lever)	022773	Screw for oscillating weight
387611	Minute wheel bridge	011145	Upper hole jewel for center wheel
388611	Setting lever spring	011146	Lower hole jewel for center wheel
391610	Second-setting lever	011306	Upper hole jewel for 3rd wheel
☆ 397610	Lever for unlocking stem	011306	Lower hole jewel for 3rd wheel
401615	Mainspring with slipping attachment	011306	Upper hole jewel for sweep second wheel
014363	Diashock upper frame	011406	Upper hole jewel for escape wheel
014364	Diashock lower frame	011406	Lower hole jewel for escape wheel
014365	Diashock hole jewel with frame	011503	Upper hole jewel for pallet
011210	Diashock cap jewel	011503	Lower hole jewel for pallet
014317	Diashock spring	011147	Upper hole jewel for transmission wheel
500613	Oscillating weight	011147	Lower hole jewel for transmission wheel
505611	Transmission wheel	023150	Tube for pallet cock screw (Cylinder type)
823611	Eccentric post	023151	Tube for bridge screw
831611	Pawl lever with jewel	023170	Tube for pallet cock screw (Recessed type)
839610	Holder for transmission wheel & pawl lever	023171	Tube for framework screw of automatic device
632610	Date corrector finger		

Remarks :

Lever for unlocking stem

☆ 397610 ... Used for the one-piece waterproof case.

If the lever for unlocking stem is required in any other type, specify the dial No. or the case No.

Date dial

☆ 801610 ... Black figures on white background } Used when the crown is located at 4 o'clock and the date frame at 3 o'clock.
 ☆ 801612 ... Black figures on gilt background }

If the date dial is required in any other type, specify ① the Cal. No. ② the crown position

③ the date frame position and ④ the dial No.

Day star with dial disk

☆ 870610 ... Used when the crown is located at 4 o'clock and the day frame at 3 o'clock.

If the day star with dial disk is required in any other type, specify the number printed on the disk.

Holding ring for dial

☆ 884611 ... Used for watches except one-piece waterproof watch.

If the holding ring for dial is required in any other type, specify the dial No. or the case No.

☆ ⇨ Please see remarks.

Items in light letters are not shown in photos.