



Cal. 7559A



- | | | | | | | |
|----------|----------|----------|----------|----------|-----------|----------------|
| | | | | | | |
| 122 750 | 131 750 | 221 750 | 225 611 | 231 750 | 241 750 | 261 611 |
| | | | | | | |
| 271 611 | 282 601 | 354 753 | 383 601 | 384 601 | 387 601 | 388 753 |
| | | | | | | |
| 390 601 | 391 750 | 701 750 | ☆801 601 | 802 601 | 803 757 | 808 601 |
| | | | | | | |
| 810 601 | 817 611 | 868 601 | ☆870 510 | 873 601 | 884 605 | 963 610 |
| | | | | | | |
| 4001 751 | 4002 753 | 4032 753 | 4050 746 | 4146 750 | ☆4219 753 | 4239 750 |
| | | | | | | |
| 4242 754 | 4259 750 | 4259 751 | 4450 753 | 4455 750 | 4455 750 | ☆Maxell SR43SW |

- | | | | | | |
|---------|---------|---------|---------|---------|---------|
| | | | | | |
| 022 257 | 022 468 | 022 491 | 022 494 | 022 760 | 022 761 |

☆⇨ Please see remarks on the next reverse page.

Cal. 7559A

Characteristics

Casing diameter : ϕ 27.0 mm
 Maximum height : 4.6 mm without battery
 Jewels : 4 j
 Frequency of quartz crystal oscillator : 32,768 Hz (Hz=Hertz Cycles per second)
 Driving system : Step motor system (2 poles)
 Regulation system : Trimmer condenser
 Second setting device
 Calendar (Day & Date)
 Instant setting device for day & date calendar
 Bilingual change-over system for day of the week
 Illuminating light : Illuminates the dial in the dark by depressing the crown.
 Battery life indicator : Second hand moves in two-second interval.

PART NO.	PART NAME	PART NO.	PART NAME
122 750	Center wheel bridge	027 866	Switch lever axle
131 750	Third wheel bridge	022 257	Setting lever spring screw
221 750	Center wheel & pinion	022 468	Center wheel bridge screw
225 611	Cannon pinion	022 468	Third wheel bridge screw
231 750	Third wheel & pinion	022 468	Circuit block screw
241 750	Fourth wheel & pinion	022 468	Screw for plus terminal of battery connection
261 611	Minute wheel		
271 611	Hour wheel	022 468	Date driving wheel screw
282 601	Clutch wheel	022 491	Minute wheel bridge screw
354 753	Winding stem	022 494	Reset lever screw
383 601	Setting lever	022 760	Day jumper screw
384 601	Yoke (Clutch lever)	022 760	Date dial guard screw
387 601	Minute wheel bridge	022 761	Dial screw
388 753	Setting lever spring	☆Maxell SR43SW	Silver oxide battery
390 601	Setting lever axle	☆U.C.C.301	
391 750	Second setting lever		
701 750	Fifth wheel & pinion		
☆801 601	Date dial		
☆801 604			
802 601	Date driving wheel		
803 757	Setting wheel lever complete		
808 601	Date dial guard		
810 601	Date jumper		
817 611	Intermediate date wheel		
868 601	Day finger		
☆870 510	Day star with dial disk		
☆870 601			
873 601	Day jumper		
884 605	Holding ring for dial		
963 610	Snap for day star with dial disk		
4001 751	Circuit block		
4002 753	Coil block		
4032 753	Bulb block		
4050 746	Circuit bridge plate		
4146 750	Step rotor		
☆4219 753	Bulb terminal insulator		
4239 750	Rotar stator		
4242 754	Plus terminal of battery connection		
4259 750	Anti-magnetic shield plate A		
4259 751	Anti-magnetic shield plate B		
4450 753	Switch lever		
4455 750	Reset lever		
011 405	Lower hole jewel for fifth wheel		
011 405	Upper hole jewel for fifth wheel		
011 537	Lower hole jewel for step rotor		
011 537	Upper hole jewel for step rotor		
023 076	Pin for anti-magnetic shield plate		

☆ ⇨ Please see remarks on the reverse page.
 Part numbers in light letters are not shown in photos.

Cal. 7559A

Remarks :

Date dial

- ☆801 601 (Black figures on white background) }
 - ☆801 604 (White figures on black background) }
- Used for both the crown and calendar frame at **3** o'clock position.

If any other type of date dial is required, specify ① Cal. No. ② The crown position ③ The calendar frame position and ④ Dial No.

Day star with dial disk

- ☆870 510 (English ↔ Spanish, black figures on white background) }
- ☆870 601 (English ↔ Spanish, white figures on black background) }

Used for both the crown and calendar frame at **3** o'clock position. If any other type of day star with dial disk is required, specify the number printed on the disk.

Bulb terminal insulator

- ☆4219 753.....When the bulb terminal insulator is adhered to the main plate, use the adhesive for glass. Refer to "**SEIKO QUARTZ TECHNICAL GUIDE**" for details.

Battery

- ☆Maxell SR43SW }
 - ☆U.C.C. 301 }
- The applied battery for this calibre might be added the substitutive in the future. In that case, please refer to separate "**BATTERIES FOR SEIKO QUARTZ WATCHES**".