

# Cyclomotion

## Watch winder

### Elma Order Nos

Cyclomotion (without clips)	103 5171
Cyclomotion pro (without clips)	103 5170
clips for 2 watches with watchstraps 165 - 205 mm	103 5190
clips for 4 watches with watchstraps 165 - 205 mm	103 5192
clips for 2 watches with watchstraps (wind up left/right) 165 - 205 mm	103 5359
clips for 4 watches with watchstraps (wind up left/right) 165 - 205 mm	103 5360
clips for 2 watches with watchstraps 150 - 165 mm	104 5571
clips for 4 watches with watchstraps 150 - 165 mm	104 5573
clips for 2 watches with watchstraps (wind up left/right) 150 - 165 mm	104 5566
clips for 4 watches with watchstraps (wind up left/right) 150 - 165 mm	104 5568
clips for 4 watches without watchstraps	103 5361
Cyclomotion wall bracket	103 5701

Fig.: Cyclomotion pro incl. clips for 12 watches with watchstraps



### The professional watch winder unit - high quality meets modern design

As an enhancement of the proven Cyclomat the new Cyclomotion series presents high-end service solutions for testing and winding of automatic watches in the workshops of watch makers and manufacturers.

#### Product features

- unit available in 2 versions, individual adjustment of the clips is possible
- change of rotational direction available, also suitable for large and heavy watches
- individually selectable clip combinations allow simultaneous winding of clockworks that wind up in one or both directions
- 2-step adjustable speed (1 or 4 rpm) for continued testing and for quick winding
- powerful, silent motor with integrated safety clutch and holding torque for a reliable protection of the watches
- optional: lockable 'Protector' cover for additional protection against dust and mechanical damage
- mechanical release screw allows the manual interruption of the service programme



**Cyclomotion**  
Watch winder.  
Version with clips for 12 watches, excluding 'Protector' cover.



**Cyclomotion pro**  
Watch winder including 'Protector' cover made of acrylic glass, with clips for 12 watches.



**Cyclomotion control board**  
Convenient and easy handling

#### Technical data

Rotational direction	left / right	Weight Cyclomotion pro (kg)	approx. 16
Rotation radial (rpm)	1 or 4	Clip (kg/pc.)	approx. 0.1
Rotation axial (rpm)	4.5 or 18	Mains voltage (VAC)	100 - 240
Cyclomotion max. W / D / H (mm)	465 / 325 / 520	Mains frequency (Hz)	50 / 60
Cyclomotion pro max. W / D / H (mm)	635 / 325 / 585	Power consumption total (W)	approx. 24
Weight Cyclomotion (kg)	approx. 11	Power consumption total standby (W)	approx. 24