

SEIZAIKEN

SILVER OXIDE BATTERY

Made in Japan



CROSS-REFERENCE CHART

Type	Dimensions		SII	Energizer	Duracell	Rayovac	Renata	Varta	SEIKO	Timex	Bulova	Citizen	Orient	IEC	
	Diameter (mm)	Height (mm)													
WATCH Battery (Low-Drain)	4.8	1.65	SR416SW	337		337	337		SB-A5		623	280-75			
	4.8	2.15	SR421SW	348					SB-A6			280-77			
	5.8	1.25	SR512SW	335		335	335	V335	SB-AB		622	280-68			
	5.8	1.65	SR516SW	317	D317	317	317	V317	SB-AR	CA	616	280-58	080-D55	SR62	
	5.8	2.15	SR521SW	379	D379	379	379	V379	SB-AC	JA	618	280-59	080-D39	SR63	
	5.8	2.70	SR527SW	319	D319	319	319	V319	SB-AE		615	280-60		SR64	
	6.8	1.45		339			339	V339							
	6.8	1.65	SR616SW	321	D321	321	321	V321	SB-AF	DA	611	280-73		SR65	
	6.8	2.15	SR621SW	364	D364	364	364	V364	SB-AG	T	602	280-34	080-D29	SR60	
	6.8	2.60	SR626SW	377	D377	377	377	V377	SB-AW	BA	606	280-39		SR66	
	7.9	1.25	SR712SW	346		346	346	V346	SB-AH		628	280-66			
	7.9	1.45	SR714SW	341			341	V341			627				
	7.9	1.65	SR716SW	315	D315	315	315	V315	SB-AT	HA	614	280-56	080-D54	SR67	
	7.9	2.10	SR721SW	362	D362	362	362	V362	SB-AK	S	601	280-29	080-D22	SR58	
	7.9	2.60	SR726SW	397	D397	397	397	V397	SB-AL	N	607	280-28	080-D20	SR59	
	7.9	3.10	SR731SW	329	D329	329	329	V329							
	7.9	3.60	SR41SW	384	D384	384	384	V384	SB-A1		247	280-18	080-D01	SR41	
	9.5	1.25	SR912SW												
	9.5	1.40											280-76		
	9.5	1.65	SR916SW	373	D373	373	373	V373	SB-AJ		617	280-45	080-D40	SR68	
9.5	2.05	SR920SW	371	D371	371	371	V371	SB-AN		605	280-31	080-D30	SR69		
9.5	2.70	SR927SW	395	D395	395	395	V395	SB-AP		610	280-48	080-D25	SR57		
9.5	3.60	SR936SW	394	D394	394	394	V394	SB-A4	LA	625	280-17		SR45		
11.6	1.65		366	D366	366	366	V366			608	280-46				
11.6	2.05	SR1120SW	381	D381	381	381	V381	SB-AS		317	280-27	080-D14	SR55		
11.6	3.05	SR1130SW	390	D390	390	390	V390	SB-AU		603	280-24	080-D15	SR54		
11.6	3.60		344	D344	344	344	V344			242			SR42		
11.6	4.20	SR43SW	301	D301	301	301	V301	SB-A8	D	226	280-01	080-D02	SR43		
11.6	5.40	SR44SW	303	D303	303	303	V303	SB-A9	A		280-08		SR44		

Type	Dimensions		SII	Energizer	Duracell	Rayovac	Renata	Varta	SEIKO	Timex	Bulova	Citizen	Orient	IEC	
	Diameter (mm)	Height (mm)													
WATCH Battery (High-Drain)	6.8	2.15		363								280-70		SR60	
	6.8	2.60	SR626W	376		376	376	V376	SB-BW	MA	619	280-72		SR66	
	7.9	1.65		314											
	7.9	2.10	SR721W	361	D317	361	361	V361	SB-BK	X		280-53	080-D32	SR58	
	7.9	2.60	SR726W	396	D396	396	396	V396	SB-BL	V	612	280-52		SR59	
	7.9	3.60	SR41W	392	D392	392	392	V392	SB-B1	K	247B	280-13	080-D05	SR41	
	7.9	5.40		393	D393		393	V393		F	255				
	9.5	1.65		372	D372								280-61		
	9.5	2.05	SW920W	370	D370	370	370	V370	SB-BN	Z	620	280-51		SR69	
	9.5	2.70	SR927W	399	D399	399	399	V399	SB-BP	W	613	280-44	080-D19	SR57	
	9.5	3.60					380								SR45
	11.6	1.65		365			365			ZA					
	11.6	2.05	SR1120W	391	D391	391	391	V391	SB-BS	L	609	280-30	080-D28	SR55	
	11.6	3.05	SR1130W	389	D389	389	389	V389	SB-BU	M	615	280-15	080-D11	SR54	
	11.6	4.20	SR43W	386	D386	386	386	V386	SB-B8	H	260	280-41	080-D04	SR43	
11.6	5.40	SR44W	357	D357	357	357	V357	SB-B9	J	288		080-D03	SR44		



Seiko Instruments Inc.

SEIZAIKEN

SILVER OXIDE BATTERY

Made in Japan



SPECIFICATIONS

Low Drain Battery

Model		Characteristics (RT)		Dimensions			C.C.V. ^{1*}	
JIS code	IEC code	Nominal Voltage (V)	Standard Discharge Current (μA)	Diameter (mm)	Height (mm)	Weight (g)	at 24°C (V)	at -10°C (V)
SR416SW	337	1.55	10	4.8	1.65	0.11	1.35	1.10
SR421SW	348	1.55	20	4.8	2.15	0.14	1.35	1.10
SR512SW	335	1.55	5	5.8	1.25	0.15	1.45	1.10
SR516SW	317	1.55	20	5.8	1.65	0.18	1.45	1.10
SR521SW	379	1.55	25	5.8	2.15	0.23	1.45	1.10
SR527SW	319	1.55	40	5.8	2.70	0.29	1.45	1.10
SR616SW	321	1.55	20	6.8	1.65	0.25	1.45	1.10
SR621SW	364	1.55	35	6.8	2.15	0.32	1.45	1.20
SR626SW	377	1.55	35	6.8	2.60	0.39	1.45	1.20
SR712SW	346	1.55	10	7.9	1.25	0.26	1.45	1.20
SR714SW	341	1.55	20	7.9	1.45	0.29	1.45	1.20
SR716SW	315	1.55	30	7.9	1.65	0.33	1.45	1.20
SR721SW	362	1.55	40	7.9	2.10	0.42	1.45	1.20
SR726SW	397	1.55	40	7.9	2.60	0.52	1.45	1.20
SR731SW	329	1.55	50	7.9	3.10	0.56	1.45	1.20
SR41SW	384	1.55	50	7.9	3.60	0.67	1.45	1.20
SR912SW	-	1.55	20	9.5	1.25	0.40	1.45	1.20
SR916SW	373	1.55	50	9.5	1.65	0.51	1.45	1.20
SR920SW	371	1.55	55	9.5	2.05	0.60	1.45	1.20
SR927SW	395	1.55	90	9.5	2.70	0.75	1.45	1.20
SR936SW	394	1.55	140	9.5	3.60	1.10	1.45	1.20
SR1120SW	381	1.55	80	11.6	2.05	0.93	1.45	1.20
SR1130SW	390	1.55	100	11.6	3.05	1.29	1.45	1.20
SR43SW	301	1.55	150	11.6	4.20	1.75	1.45	1.20
SR44SW	303	1.55	180	11.6	5.40	2.20	1.45	1.20

^{1*} C.C.V.: Closed Circuit Voltage / Low Drain 2kΩ 7.8msec Pulse

High Drain Battery

Model		Characteristics (RT)		Dimensions			C.C.V. ^{2*}	
JIS code	IEC code	Nominal Voltage (V)	Standard Discharge Current (μA)	Diameter (mm)	Height (mm)	Weight (g)	at 24°C (V)	at -10°C (V)
SR626W	376	1.55	50	6.8	2.60	0.39	1.35	0.95
SR721W	361	1.55	50	7.9	2.10	0.41	1.35	1.05
SR726W	396	1.55	50	7.9	2.60	0.52	1.35	1.05
SR41W	392	1.55	80	7.9	3.60	0.67	1.35	1.05
SR920W	370	1.55	80	9.5	2.05	0.60	1.40	1.00
SR927W	399	1.55	100	9.5	2.70	0.75	1.40	1.05
SR1120W	391	1.55	90	11.6	2.05	0.93	1.40	1.20
SR1130W	389	1.55	130	11.6	3.05	1.29	1.40	1.20
SR43W	386	1.55	220	11.6	4.20	1.75	1.40	1.20
SR44W	357	1.55	250	11.6	5.40	2.20	1.40	1.20

^{2*} C.C.V.: Closed Circuit Voltage / High Drain 200Ω 5sec DC