

CHEMSET ES 8540, ES 8541, ES 8542, ES 8543, ES 8544, ES 8545, ES 8546, ES 8547 SPECIAL EFFECT EPOXY ENAMELLING RESINS

Page: 1

Compilation date: 26/05/2017

Revision No: 1

# Section 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

# Product name: CHEMSET ES 8540, ES 8541, ES 8542, ES 8543, ES 8544, ES 8545, ES 8546, ES 8547 SPECIAL EFFECT EPOXY ENAMELLING RESINS

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

Company name: R F Bright Enterprises Ltd

Unit 6, Access 4.20

New Hythe Business Park, Bellingham Way

Aylesford

Kent

ME20 7HP

United Kingdom

**Tel:** 01622717141

Fax: 01622717163

Email: enquiries@rfbright.co.uk

## 1.4. Emergency telephone number

Emergency tel: 08450563563

# Section 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification under CLP:	Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317
Most important adverse effects:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

# 2.2. Label elements

Label elements:	
Hazard statements:	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
	H411: Toxic to aquatic life with long lasting effects.
Hazard pictograms:	GHS07: Exclamation mark
	GHS09: Environmental



CHEMSET ES 8540, ES 8541, ES 8542, ES 8543, ES 8544, ES 8545, ES 8546, ES 8547 SPECIAL EFFECT EPOXY ENAMELLING RESINS

**Page:** 2

Signal words:	Warning
Precautionary statements:	P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.
	P264: Wash hands thoroughly after handling.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P302+352: IF ON SKIN: Wash with plenty of water/soap and water.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P321: Specific treatment (see instructions on this label).

# 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

# 3.2. Mixtures

# Hazardous ingredients:

# BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-033-5	25068-38-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	50-70%
POLYGLYCIDY	ETHERS			

292-011-4	90529-77-4	-	Acute Tox. 4: H302; Skin Irrit. 2: H315	10-30%
BENZYL ALCOH	IOL			
202-859-9	100-51-6	-	Acute Tox. 4: H332; Acute Tox. 4: H302	1-10%

#### Section 4: First aid measures

#### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

CHEMSET ES 8540, ES 8541, ES 8542, ES 8543, ES 8544, ES 8545, ES 8546, ES 8547 SPECIAL EFFECT EPOXY ENAMELLING RESINS

Page: 3

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

# Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

## Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not create dust.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate

method.

## 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of dust in the air.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

storage room must be impermeable to prevent the escape of liquids.

# CHEMSET ES 8540, ES 8541, ES 8542, ES 8543, ES 8544, ES 8545, ES 8546, ES 8547 SPECIAL EFFECT EPOXY ENAMELLING RESINS

Page: 4

#### 7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

Workplace exposure limits: No data available.

**DNEL/PNEC** Values

DNEL / PNEC No data available.

#### 8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. The floor of the storage room must be
	impermeable to prevent the escape of liquids.
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency. Respiratory
	protective device with particle filter.
Hand protection:	Protective gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.

#### Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

State: Paste

Colour: Various

Odour: Characteristic odour

## 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

## 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

# CHEMSET ES 8540, ES 8541, ES 8542, ES 8543, ES 8544, ES 8545, ES 8546, ES 8547 SPECIAL EFFECT EPOXY ENAMELLING RESINS

**Page:** 5

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## **10.6. Hazardous decomposition products**

Haz. decomp. products: In combustion emits toxic fumes.

# Section 11: Toxicological information

11.1. Information on toxicological effects

## Hazardous ingredients:

# **BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}**

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

# POLYGLYCIDYETHERS

ORAL RAT LD50	1500	mg/kg
---------------	------	-------

# **BENZYL ALCOHOL**

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360	mg/kg
ORL	RAT	LD50	1230	mg/kg

#### **Relevant hazards for product:**

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

# Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

# Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# Section 12: Ecological information

# 12.1. Toxicity

Ecotoxicity values: No data available.

# CHEMSET ES 8540, ES 8541, ES 8542, ES 8543, ES 8544, ES 8545, ES 8546, ES 8547 SPECIAL EFFECT EPOXY ENAMELLING RESINS

**Page:** 6

#### 12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

# Section 13: Disposal considerations

# 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

# Section 14: Transport information

# 14.1. UN number

UN number: UN3082

# 14.2. UN proper shipping name

Shipping name: Environmentally Hazardous Substance, n.o.s.

(Epoxy Resin (number average molecular weight <700); Polyglycidylethers)

#### 14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

#### Section 15: Regulatory information

# CHEMSET ES 8540, ES 8541, ES 8542, ES 8543, ES 8544, ES 8545, ES 8546, ES 8547 SPECIAL EFFECT EPOXY ENAMELLING RESINS

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# Section 16: Other information

# Other information This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830. \* indicates text in the SDS which has changed since the last revision. Phrases used in s.2 and s.3: H302: Harmful if swallowed. H315: Causes skin irritation. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H332: Harmful if inhaled. H411: Toxic to aquatic life with long lasting effects. Legal disclaimeri The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.