

SEIZAIKEN

QUALITY OF WATCH EXPERT



SPECIFICATIONS

Low Drain Battery

Model		Nominal Voltage (V)	Dimensions		Weight (g)	C.C.V. ^{1*}	
SEIZAIKEN			Diameter (mm)	Height (mm)		at 24°C (V)	at -10°C (V)
SR416SW	337	1.55	4.8	1.65	0.11	1.35	1.10
SR421SW	348	1.55	4.8	2.15	0.14	1.35	1.10
SR512SW	335	1.55	5.8	1.25	0.15	1.45	1.10
SR516SW	317	1.55	5.8	1.65	0.18	1.45	1.10
SR521SW	379	1.55	5.8	2.15	0.23	1.45	1.10
SR527SW	319	1.55	5.8	2.70	0.29	1.45	1.10
SR616SW	321	1.55	6.8	1.65	0.25	1.45	1.10
SR621SW	364	1.55	6.8	2.15	0.32	1.45	1.20
SR626SW	377	1.55	6.8	2.60	0.39	1.45	1.20
SR712SW	346	1.55	7.9	1.25	0.26	1.45	1.20
SR714SW	341	1.55	7.9	1.45	0.29	1.45	1.20
SR716SW	315	1.55	7.9	1.65	0.33	1.45	1.20
SR721SW	362	1.55	7.9	2.10	0.42	1.45	1.20
SR726SW	397	1.55	7.9	2.60	0.52	1.45	1.20
SR731SW	329	1.55	7.9	3.10	0.56	1.45	1.20
SR41SW	384	1.55	7.9	3.60	0.67	1.45	1.20
SR912SW	-	1.55	9.5	1.25	0.40	1.45	1.20
SR916SW	373	1.55	9.5	1.65	0.51	1.45	1.20
SR920SW	371	1.55	9.5	2.05	0.60	1.45	1.20
SR927SW	395	1.55	9.5	2.70	0.75	1.45	1.20
SR936SW	394	1.55	9.5	3.60	1.10	1.45	1.20
SR1120SW	381	1.55	11.6	2.05	0.93	1.45	1.20
SR1130SW	390	1.55	11.6	3.05	1.29	1.45	1.20
SR43SW	301	1.55	11.6	4.20	1.75	1.45	1.20
SR44SW	303	1.55	11.6	5.40	2.20	1.45	1.20

^{1*} C.C.V.: Closed Circuit Voltage / Low Drain 2kΩ 7.8msec Pulse

High Drain Battery

Model		Nominal Voltage (V)	Dimensions		Weight (g)	C.C.V. ^{2*}	
SEIZAIKEN			Diameter (mm)	Height (mm)		at 24°C (V)	at -10°C (V)
SR626W	376	1.55	6.8	2.60	0.39	1.35	0.95
SR721W	361	1.55	7.9	2.10	0.41	1.35	1.05
SR726W	396	1.55	7.9	2.60	0.52	1.35	1.05
SR41W	392	1.55	7.9	3.60	0.67	1.35	1.05
SR920W	370	1.55	9.5	2.05	0.60	1.40	1.00
SR927W	399	1.55	9.5	2.70	0.75	1.40	1.05
SR1120W	391	1.55	11.6	2.05	0.93	1.40	1.20
SR1130W	389	1.55	11.6	3.05	1.29	1.40	1.20
SR43W	386	1.55	11.6	4.20	1.75	1.40	1.20
SR44W	357	1.55	11.6	5.40	2.20	1.40	1.20

^{2*} C.C.V.: Closed Circuit Voltage / High Drain 200Ω 5sec DC



Seiko Instruments Inc.
sii.co.jp/seizaiken/



CROSS-REFERENCE CHART

Type	Dimensions		SEIZAIKEN	Duracell	Rayovac	Renata	Varta	SEIKO	Timex	Bulova	Citizen	Energizer	Orient	IEC
	Diameter (mm)	Height (mm)												
WATCH Battery (Low-Drain)	4.8	1.65	SR416SW		337	337		SB-A5		623	280-75	337		
	4.8	2.15	SR421SW					SB-A6			280-77	348		
	5.8	1.25	SR512SW		335	335	V335	SB-AB		622	280-68	335		
	5.8	1.65	SR516SW	D317	317	317	V317	SB-AR	CA	616	280-58	317	080-D55	SR62
	5.8	2.15	SR521SW	D379	379	379	V379	SB-AC	JA	618	280-59	379	080-D39	SR63
	5.8	2.70	SR527SW	D319	319	319	V319	SB-AE		615	280-60	319		SR64
	6.8	1.45				339	V339					339		
	6.8	1.65	SR616SW	D321	321	321	V321	SB-AF	DA	611	280-73	321		SR65
	6.8	2.15	SR621SW	D364	364	364	V364	SB-AG	T	602	280-34	364	080-D29	SR60
	6.8	2.60	SR626SW	D377	377	377	V377	SB-AW	BA	606	280-39	377		SR66
	7.9	1.25	SR712SW		346	346	V346	SB-AH		628	280-66	346		
	7.9	1.45	SR714SW			341	V341			627		341		
	7.9	1.65	SR716SW	D315	315	315	V315	SB-AT	HA	614	280-56	315	080-D54	SR67
	7.9	2.10	SR721SW	D362	362	362	V362	SB-AK	S	601	280-29	362	080-D22	SR58
	7.9	2.60	SR726SW	D397	397	397	V397	SB-AL	N	607	280-28	397	080-D20	SR59
	7.9	3.10	SR731SW	D329	329	329	V329					329		
	7.9	3.60	SR41SW	D384	384	384	V384	SB-A1		247	280-18	384	080-D01	SR41
	9.5	1.25	SR912SW											
	9.5	1.40									280-76			
	9.5	1.65	SR916SW	D373	373	373	V373	SB-AJ		617	280-45	373	080-D40	SR68
9.5	2.05	SR920SW	D371	371	371	V371	SB-AN		605	280-31	371	080-D30	SR69	
9.5	2.70	SR927SW	D395	395	395	V395	SB-AP		610	280-48	395	080-D25	SR57	
9.5	3.60	SR936SW	D394	394	394	V394	SB-A4	LA	625	280-17	394		SR45	
11.6	1.65		D366	366	366	V366			608	280-46	366			
11.6	2.05	SR1120SW	D381	381	381	V381	SB-AS		317	280-27	381	080-D14	SR55	
11.6	3.05	SR1130SW	D390	390	390	V390	SB-AU		603	280-24	390	080-D15	SR54	
11.6	3.60		D344	344	344	V344			242		344		SR42	
11.6	4.20	SR43SW	D301	301	301	V301	SB-A8	D	226	280-01	301	080-D02	SR43	
11.6	5.40	SR44SW	D303	303	303	V303	SB-A9	A		280-08	303		SR44	

Type	Dimensions		SEIZAIKEN	Duracell	Rayovac	Renata	Varta	SEIKO	Timex	Bulova	Citizen	Energizer	Orient	IEC
	Diameter (mm)	Height (mm)												
WATCH Battery (High-Drain)	6.8	2.15									280-70	363		SR60
	6.8	2.60	SR626W		376	376	V376	SB-BW	MA	619	280-72	376		SR66
	7.9	1.65										314		
	7.9	2.10	SR721W	D317	361	361	V361	SB-BK	X		280-53	361	080-D32	SR58
	7.9	2.60	SR726W	D396	396	396	V396	SB-BL	V	612	280-52	396		SR59
	7.9	3.60	SR41W	D392	392	392	V392	SB-B1	K	247B	280-13	392	080-D05	SR41
	7.9	5.40		D393		393	V393		F	255		393		
	9.5	1.65		D372								280-61	372	
	9.5	2.05	SR920W	D370	370	370	V370	SB-BN	Z	620	280-51	370		SR69
	9.5	2.70	SR927W	D399	399	399	V399	SB-BP	W	613	280-44	399	080-D19	SR57
	9.5	3.60				380								SR45
	11.6	1.65				365			ZA			365		
	11.6	2.05	SR1120W	D391	391	391	V391	SB-BS	L	609	280-30	391	080-D28	SR55
	11.6	3.05	SR1130W	D389	389	389	V389	SB-BU	M	615	280-15	389	080-D11	SR54
	11.6	4.20	SR43W	D386	386	386	V386	SB-B8	H	260	280-41	386	080-D04	SR43
	11.6	5.40	SR44W	D357	357	357	V357	SB-B9	J	288		357	080-D03	SR44